

READ ALL INSTRUCTIONS BEFORE BEGINNING INSTALLATION

NOTICE:

Fuelpak is intended for racing use only, and is not legal for sale or use in California on pollution-controlled vehicles.

TOOLS NEEDED

- #1 Phillips Screwdriver
- #2 Phillips Screwdriver
- 1/2" Socket
- Less than 1 hour



Harley-Davidson® Dyna
Delphi® Fuel Injected Models

INSTALLATION INSTRUCTIONS FOR P/N 61005


INTRODUCTION: Congratulations on your purchase of the Fuelpak Fuel Management System for fuel injected Harley-Davidson® motorcycles. Please take the time to read the entire instruction manual before attempting to install. DO NOT adjust the Fuelpak until you have thoroughly read the instruction manual and the unit is fully installed. If you have questions, please call (562) 921-0071. **NOTICE:**

SUMMARY: To achieve the optimum performance from your application, it is recommended that you install a high performance air filter in conjunction with this unit. The Fuelpak will be installed between the factory wiring harness and the Electronic Control Unit (ECU). The Fuelpak will be mounted inside the frame opening under the seat.


PLEASE NOTE: FUELPAK USE REQUIRES A HIGH PERFORMANCE AIR FILTER.

INSTALLATION INSTRUCTIONS


1. Be sure the main and handlebar switches are in the off position during the installation process. Failure to do this will cause the "check engine" light to be set.
2. Remove left side cover exposing the Electronic Control Unit (ECU) between the seat and rear foot peg. Side cover can be removed by pulling gently.
3. Remove the seat by removing the one Phillips head screw at the back of the seat.
4. Remove the two (2) Torx screws and one (1) Allen head screw securing the electrical box. You will need to move the Data Plug to access the Allen head screw. (Fig 1)
5. Disconnect the factory connector from the ECU by pressing the latch lever and pulling. Often, this connector can be very secure.
6. Push the electrical box down, then out a couple of inches and route the factory connector to the opening in the frame under the seat. (Fig 2)
7. Route Fuelpak grey connector from the frame opening through the electrical box and connect to the factory ECU. Connect the Fuelpak black connector to the factory harness. Be sure both grey connectors are fully seated and latched.
8. Arrange connectors under ECU in electrical box so the black Fuelpak connector is against electrical box. If equipped with an audible alarm, alarm module needs to be relocated to the backbone under the ECU.
9. Reinstall electrical box. Reinstall the two Torx and one Allen head screw and tighten securely. Reinstall Data Port plug and side cover.
9. Arrange Fuelpak in frame opening so it is accessible when seat is off. For 04-06 models, place Fuelpak on top of ECU. For 2007 models, place Fuelpak between the ECU and battery.
10. You are now ready to set-up your Fuelpak.




1



2




3



4

HOW IT WORKS



ENTERING VALUES

1. Remove Fuelpak clear case cover by removing all four screws, save hardware.
2. Turn on main power and handlebar switches, but do not start engine. Fuelpak display should light up, if not, turn power off and verify the connectors are fully seated.
3. Refer to Fuelpak Map Lookup from www.fuelpakfi.com to locate the Setting Values specific to your bike and exhaust system. If you do not find your setting reference online call tech support at (562) 921-0071.
4. Starting with mode 1 selected, press the value (+) or the value (-) buttons to input the correct value as indicated in your Setting Value. After entering your first value, press the mode select button to move to mode 2 and enter the value. Continue until you have entered the value for each of the first 18 mode positions. Each time the value (+) is pressed, the value increases by one number. Each time the value (-) is pressed, the value decreases by one number. (Please refer to the "How It Works" section directly above if you have questions about this step.
5. **As the next procedure, after you have entered in your values for the first 18 modes, press the mode select button to move to mode 19. Fully twist open the throttle and return to idle position to calibrate the Fuelpak to your bike.**
6. By pressing the mode select button twice, move to mode 21 and verify that it reads "0" with the throttle closed, "50" at approximately half-throttle and "99" when fully opened; if not, repeat step 5. Do not proceed to step 7 until mode 21 is verified.
7. Enter any other mode values as required for your application.
8. Turn power off, wait one second then turn power back on. Verify all modes then turn power back off.
9. Reinstall clear cover and tuck Fuelpak into frame opening.
10. Reinstall seat and be sure front tab on seat slides into clip on frame. Tighten the Phillips head bolt at rear of seat.
11. You are now ready to ride.

IN THE EVENT OF A MALFUNCTION, PLEASE CHECK THE FOLLOWING

TECH SUPPORT

- | | |
|--|---|
| 1. Turn off main and handlebar switches then verify all connectors are fully seated. | 4. Check harness for cuts, scrapes or abrasions. |
| 2. Be sure setting values are correct for your application. | 5. Make sure the battery is fully charged and the charging system is operating correctly. |
| 3. Verify throttle calibration, step 5 in Entering Values. | 6. Call technical support at (562) 921-0071 |

WARRANTY INFORMATION

WARRANTY: Your Fuelpak unit is warranted against defects in materials and workmanship for the period of 90 days from the original retail purchase. In the event of an alleged defect in material or workmanship, Fuelpak's responsibility is strictly limited to repair or replace the defective product. Fuelpak shall not be responsible for (a) labor, transportation, or other incidental charges; (b) consequential or other damages incurred by use of any product. Fuelpak offers no other warranty beyond this limited warranty. This limited warranty does not apply to products which have been (a) modified or altered in any way; (b) subjected to adverse conditions, such as misuse, neglect, accident, improper installation

or adjustment, contaminants, corrosion, or faulty repair; or (c) used in applications other than those recommended by Fuelpak. To initiate a warranty process, the consumer must first call technical support to receive a return authorization number. The product must be returned to Fuelpak complete with a dated receipt and a return authorization number.

Fuelpak
Attn: Warranty Claims
13861 Rosecrans Avenue
Santa Fe Springs, CA 90670
(562) 921-0071